

Safety Data Sheet

according to UK REACH Regulation

KÖSTER Joint Sealant FS-H black B

Revision date: 16.11.2021

Product code: J_232_B

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

KÖSTER Joint Sealant FS-H black B

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

The product is intended for professional use. Building and construction work.

Uses advised against

No identified use(s).

1.3. Details of the supplier of the safety data sheet

Company name:	KÖSTER BAUCHEMIE AG	
Street:	Dieselstrasse 1 - 10	
Place:	D-26607 Aurich	
Telephone:	+49-4941-9709-0	Telefax: +49-4941-9709-40
e-mail:	info@koester.eu	
Contact person:	Forschung & Entwicklung	
e-mail:	produktsicherheit@koester.eu	
Internet:	www.koester.eu	

1.4. Emergency telephone number:

+49-551-19240 (24 h, Giftinformationszentrum Nord)


SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Acute Tox. 4; H302
Acute Tox. 4; H332
Skin Sens. 1; H317
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**

manganese dioxide
thiram (ISO); tetramethylthiuram disulphide
1,3-diphenylguanidine

Signal word: Warning**Pictograms:****Hazard statements**

H302 Harmful if swallowed.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.

Safety Data Sheet

according to UK REACH Regulation

KÖSTER Joint Sealant FS-H black B

Revision date: 16.11.2021

Product code: J_232_B

Page 2 of 10

P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P350	IF ON SKIN: Gently wash with plenty of soap and water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Adhesives, sealants

Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification (GB CLP Regulation)	
1313-13-9	manganese dioxide	< 25 %
	215-202-6	025-001-00-3
	Acute Tox. 4, Acute Tox. 4; H332 H302	
27138-31-4	Oxydipropyl dibenzoate	20 - < 40 %
	248-258-5	01-2119529241-49
	Aquatic Chronic 3; H412	
137-26-8	thiram (ISO); tetramethylthiuram disulphide	< 2,5 %
	205-286-2	006-005-00-4
	Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT RE 2, Aquatic Acute 1, Aquatic Chronic 1; H332 H302 H315 H319 H317 H373 H400 H410	
102-06-7	1,3-diphenylguanidine	< 1 %
	203-002-1	612-149-00-4
	Repr. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, Aquatic Chronic 2; H361f H302 H315 H319 H335 H411	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1313-13-9	215-202-6	manganese dioxide	< 25 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: ATE = 500 mg/kg	
27138-31-4	248-258-5	Oxydipropyl dibenzoate	20 - < 40 %
		inhalation: LC50 = 200 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 3914 mg/kg	
137-26-8	205-286-2	thiram (ISO); tetramethylthiuram disulphide	< 2,5 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: ATE = 500 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10	
102-06-7	203-002-1	1,3-diphenylguanidine	< 1 %
		oral: ATE = 500 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

Safety Data Sheet

according to UK REACH Regulation

KÖSTER Joint Sealant FS-H black B

Revision date: 16.11.2021

Product code: J_232_B

Page 3 of 10

General information

First aider: Pay attention to self-protection! Move victim out of danger zone.

After inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Medical treatment necessary.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings. Suitable extinguishing media: dry extinguishing powder. Foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Special exposure hazards arising from the substance itself, combustion products, resulting gases: Carbon dioxide. Carbon monoxide

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protective suit.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation. Avoid contact with skin, eyes and clothes. Wear personal protection equipment. Move victim out of danger zone.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**Other information**

Take up mechanically. Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

Safety Data Sheet

according to UK REACH Regulation

KÖSTER Joint Sealant FS-H black B

Revision date: 16.11.2021

Product code: J_232_B

Page 4 of 10

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Wear suitable protective clothing and gloves.

Advice on protection against fire and explosion

No special technical protective measures are necessary.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

Further information on handling

Keep only in the original container in a cool, well-ventilated place. Wear suitable gloves.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep/Store only in original container. Keep in a cool place.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Keep in a cool place. Protect from sunlight.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
-	Manganese: its inorganic compounds (as Mn, inhalable fraction)	-	0.2		TWA (8 h)	WEL

8.2. Exposure controls

Appropriate engineering controls

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Suitable material: NBR (Nitrile rubber). Butyl rubber. Breakthrough times and swelling properties of the material must be taken into consideration.

Skin protection

Chemical resistant suit. Only wear fitting, comfortable and clean protective clothing.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Safety Data Sheet

according to UK REACH Regulation

KÖSTER Joint Sealant FS-H black B

Revision date: 16.11.2021

Product code: J_232_B

Page 5 of 10

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Paste	
Colour:	pigmented	
Odour:	characteristic	
Flash point:		> 100 °C
Density:		1,7 g/cm ³

9.2. Other information**Information with regard to physical hazard classes**

Explosive properties
not explosive.
Oxidizing properties
Not oxidising.

Other safety characteristics

Solid content: not determined
Viscosity / dynamic: viscous structure.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No risks worthy of mention.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No risks worthy of mention.

10.4. Conditions to avoid

No risks worthy of mention.

10.5. Incompatible materials

No risks worthy of mention.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Toxicokinetics, metabolism and distribution**

No information available.

Acute toxicity

Harmful if inhaled. Harmful if swallowed.

ATEmix calculated

ATE (oral) 961,5 mg/kg; ATE (inhalation dust/mist) 2,941 mg/l

Safety Data Sheet

according to UK REACH Regulation

KÖSTER Joint Sealant FS-H black B

Revision date: 16.11.2021

Product code: J_232_B

Page 6 of 10

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1313-13-9	manganese dioxide				
	oral	ATE 500 mg/kg			
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
27138-31-4	Oxydipropyl dibenzoate				
	oral	LD50 3914 mg/kg	Rat	ECHA	
	dermal	LD50 > 2000 mg/kg	Rat	ECHA	
	inhalation (4 h) dust/mist	LC50 200 mg/l	Rat	ECHA	
137-26-8	thiram (ISO); tetramethylthiuram disulphide				
	oral	ATE 500 mg/kg			
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
102-06-7	1,3-diphenylguanidine				
	oral	ATE 500 mg/kg			

Information on likely routes of exposure

ingestion.
inhalation.

Specific effects in experiment on an animal

No information available.

Additional information on tests

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
27138-31-4	Oxydipropyl dibenzoate					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Alburnus alburnus	ECHA	
	Acute algae toxicity	ErC50 > 3,2 mg/l	96 h	Pseudokirchneriella subcapitata	ECHA	
	Acute crustacea toxicity	EC50 0,0059 mg/l	48 h	Daphnia magna	ECHA	
	Fish toxicity	NOEC > 0,125 mg/l	14 d	Alburnus alburnus	ECHA	
	Crustacea toxicity	NOEC 0,01 mg/l	21 d	Daphnia magna	ECHA	

Safety Data Sheet

according to UK REACH Regulation

KÖSTER Joint Sealant FS-H black B

Revision date: 16.11.2021

Product code: J_232_B

Page 7 of 10

12.2. Persistence and degradability

Product is not easily biodegradable.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
27138-31-4	Oxydipropyl dibenzoate			
	Evolution	78 %	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

No information available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
27138-31-4	Oxydipropyl dibenzoate	3,9

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

No information available.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

UN3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Thiram (vgl. Bis(dimethyl-thiocarbamoyl)disulfid)/ Oxydipropyldibenzoat)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9



Classification code:

M6

Safety Data Sheet

according to UK REACH Regulation

KÖSTER Joint Sealant FS-H black B

Revision date: 16.11.2021

Product code: J_232_B

Page 8 of 10

Special Provisions: 274 335 601
 Limited quantity: 5 L
 Transport category: 3
 Hazard No: 90
 Tunnel restriction code: E

Other applicable information (land transport)

E1

Inland waterways transport (ADN)

14.1. UN number or ID number: UN3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Thiram (vgl. Bis(dimethyl-thiocarbamoyl)disulfid)/ Oxydipropyldibenzoat)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9



Classification code: M6
 Special Provisions: 274 335 601
 Limited quantity: 5 L

Other applicable information (inland waterways transport)

E1

Marine transport (IMDG)


14.1. UN number or ID number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (thiram/ oxydipropyl dibenzoate)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9



Special Provisions: 274, 335, 969
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (thiram/ oxydipropyl dibenzoate)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9



Special Provisions: A97 A158 A197 A215
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y964
 Excepted quantity: E1

Safety Data Sheet

according to UK REACH Regulation

KÖSTER Joint Sealant FS-H black B

Revision date: 16.11.2021

Product code: J_232_B

Page 9 of 10

IATA-packing instructions - Passenger:	964
IATA-max. quantity - Passenger:	450 L
IATA-packing instructions - Cargo:	964
IATA-max. quantity - Cargo:	450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: Thiram/ oxydipropyl dibenzoate

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):
Entry 75

2004/42/EC (VOC): 45 %

National regulatory information

Water hazard class (D): 3 - highly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,14.

Abbreviations and acronyms

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organization
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- OSHA: Concerning the International Transport of Dangerous Goods by Rail)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- NOEL: No observed effect level
- NOAEL: No observed adverse effect level
- LOAEL: Lowest observed adverse effect level
- NOAEC: No observed adverse effect level
- LOAEC: Lowest observed adverse effect concentration
- DNEL: Derived No Effect Level
- PNEC: predicted no effect concentration
- TSCA: Toxic Substances Control Act
- IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
- NTP: National Toxicology Program
- SARA: Superfund Amendments and Reauthorization Act

Safety Data Sheet

according to UK REACH Regulation

KÖSTER Joint Sealant FS-H black B

Revision date: 16.11.2021

Product code: J_232_B

Page 10 of 10

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

PBT: Persistent bioaccumulative toxic

SVHC: substance of very high concern

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Acute Tox. 4; H332	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)