

PRODUCT DATA SHEET

Delta Glass PC F Anchor



Description

Delta Glass PC F Anchor is a unique stainless-steel anchor fixing which enables complete continuation of Delta Glass insulation to the wall and soffit on installation.

Suitable for supported and accepting of screw nail anchor substrates. Mechanical fastening is carried out with a screw nail which remains covered. This prevents the vapour-proof Delta Glass insulation from being penetrated. The system will remain free from thermal bridging.

Fields of Application

- Fixing Delta Glass Insulation

Storage

- Store safely and keep out of reach of children
- Always store and transport in a secure position

Associated Products

- Delta Glass Floor Board T4+

Product Details

DMS Special Order

Technical Data

Delta Glass PC F Anchor

Type	Stainless Steel 1.4301 (EN 10088-2)
Basis	Stainless Steel
Thickness	0.7mm
Surface Quality	2 B
Tolerances Standard	EN ISO 9445: 2006
Contents/Packaging	Box of 100

Other Information

All data and information contained in these Product/Technical Data Sheets is up-to-date and correct as at the date of issue. The information given is suggested as guidance and should only be used for evaluating your specific application. Delta Membrane Systems Limited cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. The information contained in these Product/Technical Data Sheets should not be considered a warranty, expressed, or implied, including but not limited to a warranty of merchantability or fitness for a particular purpose. In no event shall Delta Membrane Systems Limited be liable for any incidental or consequential damages resulting from the use, misuse, or inability to use the product. This exclusion applies regardless of whether such damages are sought based on breach of warranty, breach of contract, negligence, strict liability in tort, or any other legal theory. When in doubt, contact Delta's Technical Team on 01992 523 523.

