NDELTA

PRODUCT DATA SHEET

Delta Amphibia Pressure Corners



Description

Typically, Delta Amphibia Pressure Corners are used in slab edge preparation. Generally, Delta Amphibia Pressure Corner 90° is applied to the outside edge of formworks pre concrete pour with Delta Amphibia Pressure Corner 270° being applied to the inside edge of formwork pre concrete pour for continuity around toes in concrete slabs.

Delta Amphibia is a unique Self-Healing/Repairing, Self-Sealing, fully bonded Type A waterproofing membrane, utilising its advanced Reactive Core technology, Delta Amphibia will not only Self-Repair in the event of accidental puncture and Self-Heal, but will also Self-Seal.

DMS

DMS

Colour

Lenath

Height

Technical Data

Contents/Packaging

Delta Amphibia Pressure Corners

1038 Pressure Corner 90°

1039 Pressure Corner 270°

Black

1.5m

5cm x 10cm

10 Pieces

Fields of Application

Continuity of Delta Amphibia Membranes

Specification

- BS 8102:2022 Protection of below ground structures against water ingress. Code of practice.
- NBS J40 / 130 Flexible Sheet Tanking / waterproofing

Associated Products

- Delta Amphibia Membranes
- Delta Amphibia AKTI-VO 201
- Delta Amphibia BI Mastic
- Delta Amphibia Pressure Corner 90°
- Delta Amphibia Pressure Line

Product Details

DMS 1038 – Delta Amphibia Pressure Corner 90° DMS 1039 – Delta Amphibia Pressure Corner 270°

Other Information

All data and information contained in these Product/Technical Data Sheets is up-to-date and correct as at the date of issue. The information given is suggested as guidance and should only be used for evaluating your specific application. Delta Membrane Systems Limited cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. The information contained in these Product/Technical Data Sheets should not be considered a warranty, expressed, or implied, including but not limited to a warranty of merchantability or fitness for a particular purpose. In no event shall Delta Membrane Systems Limited be liable for any incidental or consequential damages resulting from the use, misuse, or inability to use the product. This exclusion applies regardless of whether such damages are sought based on breach of warranty, breach of contract, negligence, strict liability in tort, or any other legal theory. When in doubt, contact Delta's Technical Team on 01992 523 523.

<u>UK</u>

