



Description

Delta Aquaduct is an external land drain coil. Installed externally to direct ground water into a sump or soak away and reduce pressure from bearing on the structure.

Delta Aquaduct is perforated for maximum performance and incorporates an outer geotextile filter to prevent particles from entering the conduit system. Available in 2 lengths/widths with complimentary connectors also available ((please see below table for DMS codes) also referred to as couplers or joiners) to connect multiple coils of Delta Aquaduct together.

This ideal, cost-effective external drainage option is suitable for most projects. Delta Aquaduct coil is designed for excellent water flow and allows for easy maintenance and inspection.

Features

- Used as a collector drain for the removal of excess surface water
- Excellent water flow
- Fast and easy installation
- Perforated for maximum performance
- Outer geotextile filter to prevent particles entering conduit system
- Corrugated for extra strength

Packaging

Supplied in 60mm x 50m rolls – Aquaduct 60
Supplied in 100mm x 50m rolls – Aquaduct 100

Product Details

DMS078-1	Aquaduct 60 (60mm x 50m)
DMS 085	Aquaduct 100 (100mm x 50m)
DMS 087	Aquaduct 60mm Straight Connectors
DMS 089	Aquaduct 60mm T-Piece Connector
DMS 095	Aquaduct 100mm T-Piece Connectors
DMS 096	Aquaduct 100mm Straight Connectors
DMS 098	Aquaduct 100mm Y-Piece Connector
DMS 102	Aquaduct 60mm Y-Piece Connectors
DMS 145	Aquaduct 60 End Caps (red/Blue bung)

Fields of Application

- Below Ground Structures
- Agriculture
- Playing fields
- Recreational areas
- Roads
- Embankments
- Maintainable Land Drains

Specification

- R16/340 Pipes, bends and junctions – PVC-U – Corrugated Perforated
- R12/344 Pipes, bends and junctions - plastics - structured wall
- R12/14 Pipes, bends and junctions – PVC-U – solid wall
- PR_65_52_07_88

Associated Products

- Delta Floraxx Top
- Delta Terraxx
- Delta Geo-Drain Quattro
- External Drainage Membranes



Installation

Please refer to the Delta Installation Guides. Installation Guides can be found at www.deltamembranes.com/technical/delta-installation-guides/. We have a number of "How to" subject related video guides available on your Youtube Channel and Website. Please visit www.deltamembranes.com/technical-categories/the-video-suite/

Storage

- Store safely and keep out of reach of children
- Always store and transport in a secure upright position

Guarantees

Delta Membrane Systems Limited offer a 30-year Product Guarantee on membranes, seals and fixings when a Delta Cavity Drain System has been installed by a Delta Registered Installer. A list of experienced Delta Registered Installers is available from Delta's offices.

Safety

Always follow the instructions provided in the material safety data sheet and take the precaution described there. Wear appropriate Protective Personal Equipment (PPE) when applying and using the material. Observe all governmental, state, and local safety regulations when processing the material.

Other Information

All data and information contained in these Product/Technical Data Sheets is up-to-date and correct as at the date of issue. The information given is suggested as guidance and should only be used for evaluating your specific application. Delta Membrane Systems Limited cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. The information contained in these Product/Technical Data Sheets should not be considered a warranty, expressed, or implied, including but not limited to a warranty of merchantability or fitness for a particular purpose. In no event shall Delta Membrane Systems Limited be liable for any incidental or consequential damages resulting from the use, misuse, or inability to use the product. This exclusion applies regardless of whether such damages are sought based on breach of warranty, breach of contract, negligence, strict liability in tort, or any other legal theory. When in doubt, contact Delta's Technical Team on 01992 523 523.

