PRODUCT DATA SHEET

Delta Inspection Ports (Jetting Eyes)



Description

Delta Inspection Ports are designed for use with Delta perimeter drainage channel (with or without upstand DMS 207/DMS 208). Delta Inspection Ports allow for maintenance and future cleaning/ flushing of the basement drainage system (with a suitable anti-lime solution (if required)).

Delta Inspection Ports easily connect to Delta drainage channels. Delta Inspection Ports should be included in the perimeter drainage channel at every change of direction.

Where Perimeter Drainage Channel is incorporated into a Type C, cavity drained system we recommend a minimum of 1 sump per 50 linear metres of channel.

Features

- For ease of cleaning, inspection, and maintenance of perimeter drainage channel
- · Easily removes any blockages in perimeter drainage channel
- Easily flushes out debris from perimeter drainage channel
 Compatible with Delta perimeter drainage channel and
- ancillaries
- Compatible with Delta Type C Cavity Drained Protection
 Systems

Fields of Application

- Where there is a change of direction in perimeter drainage channel
- For all basement drainage systems where perimeter drainage channel is included

Product Details

Other Information

DMS 094


Specification

- BS 8102:2022 Protection of below ground structures against water ingress. Code of practice.
- NBS Specification R18 (Clause 310) Pumping Stations and Pressure Pipelines

Associated Products

- Delta Channel without Upstand
- Delta Channel with Upstand
- Delta Basement Drainage

Technical Drawing - DW-242-3-(C)



All data and information contained in these Product/Technical Data Sheets is up-to-date and correct as at the date of issue. The information given is suggested as guidance and should only be used for evaluating your specific application. Delta Membrane Systems Limited cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. The information contained in these Product/Technical Data Sheets should not be considered a warranty, expressed, or implied, including but not limited to a warranty of merchantability or fitness for a particular purpose. In no event shall Delta Membrane Systems Limited be liable for any incidental or consequential damages resulting from the use, misuse, or inability to use the product. This exclusion applies regardless of whether such damages are sought based on breach of warranty, breach of contract, negligence, strict liability in tort, or any other legal theory. When in doubt, contact Delta's Technical Team on 01992 523 523.